

Taking care of people, our masterpieces

# Duetto MT EVO


Alexandrite and Nd:YAG Lasers Combined with Mixed Technology



# **DUETTO MT EVO**

# NEW "NO COMPROMISE" TECHNOLOGY

**Duetto MT EVO** laser combines two laser wavelengths (755 and 1064 nm) in a single emission with programmable fluence, pulse duration and adjustable sequencies to increase the treatment's safety and effectiveness.



**Duetto MT EVO** performs the largest range of hair reduction\* applications, as well as vascular and rejuvenation treatments. Due to the wavelength and pulse **M**ixed **Technology**, **Duetto MT EVO** allows operator to select single or double wavelength emissions, using simultaneous or sequential pulses that can be adjusted according to the patient's needs.

**Duetto MT EVO** is the final solution for the professionals of the aesthetic medicine market, enabling tailored treatments with no compromise between safety and effectiveness. A full set of handpieces is available on request.

### **ACCESSORIES & OPTIONS**

### **TWAIN 2940**

Twain 2940 is a laser handpiece that fits to the Twain universal connector present on the Quanta System laser platforms. It has been designed to perform ablation procedures, both fractional and homogeneous. The Er:YAG laser @ 2940 nm is able, through the variation of pulse parameters, to remove the layers of skin with minimal thermal damage or produce a higher coagulation suitable for the stimulation of collagen production.



FRACTIONAL skin resurfacing traumatic and acne scars epidermal dyschromia sun and age spots

HOMOGENOUS skin ablation full skin resurfacing

### TWAIN IPL

Duetto MT EVO can be equipped with Twain IPL handpieces. The contact skin cooling and the 6 range of wavelengths available, expand flexibility and versatility in the treatments.

permanent hair reduction benign pigmented lesions skin rejuvenation procedures dermatological vascular treatments active acne



# **Integrated Contact SKIN COOLER**

The skin cooler is fully integrated into the system. In all protocols performed with pulsed lasers, it ensures an efficient thermal protection and increases the treatment comfort.



### **SKINCRYO**

It is an adapter that integrates the optics of pulsed laser with Zimmer air cooling. This handpiece ensures the best pain reduction when treating large areas.



<sup>\*</sup> Permanent hair reduction is defined as the long-term stable reduction in the number of hairs regrowing when measured at 6, 9, and 12 months after the completion of a treatment regimen.

# RESULTS BEFORE / AFTER



COMPARATIVE PERMANENT HAIR REDUCTION 755 nm - 755+1064 nm Courtesy Paolo Sbano MD



COMPARATIVE PERMANENT HAIR REDUCTION
755 nm - 755+1064 nm Post 2 treatments, follow-up 4 months

Courtesy Paolo Sbano MD





SKIN REJUVENATION

Courtesy Dhami MD





PERMANENT HAIR REDUCTION

Courtesy Paolo Sbano MD





VASCULAR LESIONS LEGS Courtesy Emilio Bonizzoni MD





SPIDER ANGIOMA Courtesy Emilio Bonizzoni MD

## TECHNICAL SPECIFICATIONS

Laser		Nd:YAG Pulsed	Alexandrite Pulsed	Nd:YAG + Alexandrite Pulsed				
Wavelength	(nm)	1064	755	1064 + 755				
Pulse width	(ms)	0.3 ÷ 300*	0.3 ÷ 300*	0.3 ÷ 300*				
Burst mode		up to 3 pulses Ton and Toff adjustable	up to 3 pulses Ton and Toff adjustable	up to 3 pulses Ton and Toff adjustable only for simultaneous mode				
Beam delivery		optical fiber with detachable handpiece						
Spot size (optional)	(mm)	2 ÷ 16	6 ÷ 16	2 ÷ 18				
Max fluence	(J/cm <sup>2</sup> )	500 (software limited)	500 (software limited)	500 A + 500 Y (software limited)				
Repetition rate	(Hz)	up to 10	up to 10	up to 5				
Skin Cooling system		integrated skin cooler (optional) or air cooling handpiece adaptor (optional)						
Electrical requirements		3.7 kVA, 200-240 Vac; 50/60 Hz						
Dimensions and weight		530(W) x 1043 (D) x 1060 (H) mm <sup>3</sup> ; 150 Kg						
Notes		* the pulse-width range can change depending on repetition rate and mix mode configuration						

The certified model name is: Duetto MT

OPTION Twain 2940			Twain IPL						
Source		Er:YAG	IPL handpieces						
Wavelength	(nm)	2940	650-1200	625-1200	590-1200	570-1200	550-1200	400-1200	
Pulse width	(ms)	0.3÷1	5 - 40 (pulses train duration up to 240 ms)						
Repetition rate	(Hz)	up to 6	0,5						
Spot size	(mm)	2, 4, 9 mm + fractionated	48x13 or 25x13 mm <sup>2</sup>						
Fluence	(J/cm <sup>2</sup> )	up to 10	up to 25						

### VISIBLE AND INVISIBLE LASER RADIATION

Avoid eye skin exposure to direct or scattered radiation Laser product: Class 4 Aiming beam: Class 3R







Note: National local authorities may put restrictions to the parameters indicated in the above table, or may limit or remove certain intended uses. Specifications are subject to change without notice.

Quanta System products are manufactured according to the International standards and have been cleared by the most important International notified bodies. The Company is EN ISO 9001:2008 and EN ISO 13485:2012 certified. Quanta System S.p.A. was founded in 1985 and belongs to the EI. En. Group (a public company listed in the Star segment of the Italian Stock Exchange) since January 2004. The company, divided into three business units (medical, scientific and industrial) is specialized in manufacturing of laser and opto-electronic devices.



